





EasyExo is a soft passive exoskeleton that is designed to provide assisted support to the user without the need for an external power source. EasyExo supports posture correction by providing intra-abdominal pressure to the user's lower back. This helps protect against strain and injury, enhancing productivity, safety, and overall ergonomics.

KEY BENEFITS



Musculoskeletal Support

Provides "assisted-power" to reduce musculoskeletal strain on the user; ensuring that the user maintains the correct posture when carrying out physical activities.

Comfortable Fit

To provide form-fitting experience without hindering the user's mobility.

Lightweight and Durable

Incorporating our lightweight, high-strength TITAN laminate. It is also abrasion resistant, enabling operations in various environments.

Note: EasyExo DOES NOT give the user extra strength or energy to carry or lift heavier items.

APPLICABLE INDUSTRIES













KEY FEATURES

Chest Strap

Provides upper body stability & prevents slouching

Belly Strap

Stabilises the lower back & supports load transfer

Thigh Strap

Supports load transfer to the legs & assists joint alignment (hip & knee)




Harness


Supports spine & prevents excessive bending

Y-Elastic

Allows natural movement & flexibility while providing secure fit

PERFORMANCE





Reduction in Lower Back Muscle Activation

Weight is redistributed to the upper leg area, resulting in an increased muscle activation (REDUCED: 20% at Lumbar and 17% at Thoracic, INCREASED: 11% at Hamstring and 7% at Thigh).

PRODUCT SPECIFICATIONS

Colours [Model No.]	Black [180J9100], Yellow [180J9111]
Base Fabric Material	Polyester, Nylon, TITAN Laminated Fabric
Fabric Tensile Strength	> 2300 N
Webbing Material	Polyester
Webbing Tensile Strength	> 4890 N
Elastic Band Tensile Strength	2050 N
Water Repellency Spray Test	Rate 5
Oil Repellency	Rate 4
Velcro Peel Strength	> 3.0 N/cm
Thread Material	Polyester
Sizing	Size 1: S - XL, Size 2: L - 3XL
Mass	Size 1: 1 kg, Size 2: 1.1 kg
Operating Temperature	10 °C to 50 °C

Note: Specifications are subject to change by the manufacturer without prior notice. Pictures shown are for illustrative purposes only, actual product may vary.

